


Product Data Sheet

Midland Brick

A BORAL COMPANY

CLAY FACE BRICK

Cream Mexi Midland Creams



Product Information	Cored	Solid
Work Size (mm)	230 x 110 x 76	230 x 110 x 76
Dimensional Category	DW1	DW1
Approximate Unit Weight (kg)	2.7	3.7
Approximate No. per m ²	48.5	48.5
No. Per Pack	264	264
Pack Weight (kg) ¹	734	1006
Characteristic Unconfined Compressive Strength (MPa) <i>f'</i> _{uc}	>12	>12
Cold Water Absorption (%)	<12	<12
Coefficient of Expansion (mm/m)	<0.8	<0.8
Durability Class	Exposure Grade	Exposure Grade
Initial Rate of Absorption (kg/m ² /min)	<1.6	<1.6
Potential to Effloresce	Nil-Slight	Nil-Slight
Liability to Lime Pitting	Nil	Nil
Core Percentage	<30	-
Solar Absorption Rating	Low	Low
Fire Resistance – Insulation (minutes)	90	90

This technical information represents average properties obtained from production runs. If specific results are required, samples should be taken from current production runs. AS/NZS 4456 and 4586 are used as applicable. Durability classifications are based on product knowledge under local (Perth) climatic condition. Colours are indicative only. Information subject to change without notice.

¹Includes +3% moisture

Midland Creams – Clay Face Bricks



Cream Mexi




Cream Mexi Coach



Cream Smooth



Desert Oak



Limestone Hue



Milano



Seville



Tuscan

Note: If you require specific or improved product specifications please contact your Sales Representative.

DISCLAIMER. The information presented herein is supplied in good faith and to the best of our knowledge was correct at the time of preparation. No responsibility can be accepted by Midland Brick Company Pty Ltd, its staff or its agents for any errors or omissions. Users are advised to make their own determination as to the suitability of this information in relation to their particular purposes and specific circumstances. Since the information contained in this document may be applied under conditions beyond our control, no responsibility can be accepted by Midland Brick Company Pty Ltd, its staff or its agents for any loss or damage caused by any person acting or refraining from action as a result of this information.


Product Data Sheet

Midland Brick

A BORAL COMPANY

CLAY FACE BRICK

Cream Mexi Coach Midland Creams



Product Information	Cored	Solid
Work Size (mm)	230 x 110 x 76	230 x 110 x 76
Dimensional Category	DW1	DW1
Approximate Unit Weight (kg)	2.7	3.7
Approximate No. per m ²	48.5	48.5
No. Per Pack	264	264
Pack Weight (kg) ¹	734	1006
Characteristic Unconfined Compressive Strength (MPa) <i>f'</i> _{uc}	>12	>12
Cold Water Absorption (%)	<12	<12
Coefficient of Expansion (mm/m)	<0.8	<0.8
Durability Class	Exposure Grade	Exposure Grade
Initial Rate of Absorption (kg/m ² /min)	<1.6	<1.6
Potential to Effloresce	Nil-Slight	Nil-Slight
Liability to Lime Pitting	Nil	Nil
Core Percentage	<30	-
Solar Absorption Rating	Low	Low
Fire Resistance – Insulation (minutes)	90	90

This technical information represents average properties obtained from production runs. If specific results are required, samples should be taken from current production runs. AS/NZS 4456 and 4586 are used as applicable. Durability classifications are based on product knowledge under local (Perth) climatic condition. Colours are indicative only. Information subject to change without notice.

¹Includes +3% moisture

Midland Creams – Clay Face Bricks




Cream Mexi



Cream Mexi Coach



Cream Smooth



Desert Oak



Limestone Hue



Milano



Seville



Tuscan

Note: If you require specific or improved product specifications please contact your Sales Representative.

DISCLAIMER. The information presented herein is supplied in good faith and to the best of our knowledge was correct at the time of preparation. No responsibility can be accepted by Midland Brick Company Pty Ltd, its staff or its agents for any errors or omissions. Users are advised to make their own determination as to the suitability of this information in relation to their particular purposes and specific circumstances. Since the information contained in this document may be applied under conditions beyond our control, no responsibility can be accepted by Midland Brick Company Pty Ltd, its staff or its agents for any loss or damage caused by any person acting or refraining from action as a result of this information.


Product Data Sheet

Midland Brick

A BORAL COMPANY

CLAY FACE BRICK

Cream Smooth Midland Creams



Product Information	Cored	Solid
Work Size (mm)	230 x 110 x 76	230 x 110 x 76
Dimensional Category	DW1	DW1
Approximate Unit Weight (kg)	2.7	3.7
Approximate No. per m ²	48.5	48.5
No. Per Pack	264	264
Pack Weight (kg) ¹	734	1006
Characteristic Unconfined Compressive Strength (MPa) <i>f'</i> _{uc}	>12	>12
Cold Water Absorption (%)	<12	<12
Coefficient of Expansion (mm/m)	<0.8	<0.8
Durability Class	Exposure Grade	Exposure Grade
Initial Rate of Absorption (kg/m ² /min)	<1.6	<1.6
Potential to Effloresce	Nil-Slight	Nil-Slight
Liability to Lime Pitting	Nil	Nil
Core Percentage	<30	-
Solar Absorption Rating	Low	Low
Fire Resistance – Insulation (minutes)	90	90

This technical information represents average properties obtained from production runs. If specific results are required, samples should be taken from current production runs. AS/NZS 4456 and 4586 are used as applicable. Durability classifications are based on product knowledge under local (Perth) climatic condition. Colours are indicative only. Information subject to change without notice.

¹Includes +3% moisture

Midland Creams – Clay Face Bricks



Cream Mexi



Cream Mexi Coach




Cream Smooth



Desert Oak



Limestone Hue



Milano



Seville



Tuscan

Note: If you require specific or improved product specifications please contact your Sales Representative.

DISCLAIMER. The information presented herein is supplied in good faith and to the best of our knowledge was correct at the time of preparation. No responsibility can be accepted by Midland Brick Company Pty Ltd, its staff or its agents for any errors or omissions. Users are advised to make their own determination as to the suitability of this information in relation to their particular purposes and specific circumstances. Since the information contained in this document may be applied under conditions beyond our control, no responsibility can be accepted by Midland Brick Company Pty Ltd, its staff or its agents for any loss or damage caused by any person acting or refraining from action as a result of this information.


Product Data Sheet

Midland Brick

A BORAL COMPANY

CLAY FACE BRICK

Desert Oak Midland Creams



Product Information	Cored	Solid
Work Size (mm)	230 x 110 x 76	230 x 110 x 76
Dimensional Category	DW1	DW1
Approximate Unit Weight (kg)	2.7	3.6
Approximate No. per m ²	48.5	48.5
No. Per Pack	264	264
Pack Weight (kg) ¹	734	979
Characteristic Unconfined Compressive Strength (MPa) <i>f'uc</i>	>10	>10
Cold Water Absorption (%)	<15	<15
Coefficient of Expansion (mm/m)	<0.8	<0.8
Durability Class	General Purpose	General Purpose
Initial Rate of Absorption (kg/m ² /min)	<1.6	<1.6
Potential to Effloresce	Nil-Slight	Nil-Slight
Liability to Lime Pitting	Nil	Nil
Core Percentage	<30	-
Solar Absorption Rating	Low to Medium	Low to Medium
Fire Resistance – Insulation (minutes)	90	90

This technical information represents average properties obtained from production runs. If specific results are required, samples should be taken from current production runs. AS/NZS 4456 and 4586 are used as applicable. Durability classifications are based on product knowledge under local (Perth) climatic condition. Colours are indicative only. Information subject to change without notice.

¹Includes +3% moisture

Midland Creams – Clay Face Bricks



Cream Mexi



Cream Mexi Coach




Cream Smooth



Desert Oak



Limestone Hue



Milano



Seville



Tuscan

Note: If you require specific or improved product specifications please contact your Sales Representative.

DISCLAIMER. The information presented herein is supplied in good faith and to the best of our knowledge was correct at the time of preparation. No responsibility can be accepted by Midland Brick Company Pty Ltd, its staff or its agents for any errors or omissions. Users are advised to make their own determination as to the suitability of this information in relation to their particular purposes and specific circumstances. Since the information contained in this document may be applied under conditions beyond our control, no responsibility can be accepted by Midland Brick Company Pty Ltd, its staff or its agents for any loss or damage caused by any person acting or refraining from action as a result of this information.


Product Data Sheet

Midland Brick

A BORAL COMPANY

CLAY FACE BRICK

Limestone Hue Midland Creams



Product Information	Cored	Solid
Work Size (mm)	230 x 110 x 76	230 x 110 x 76
Dimensional Category	DW1	DW1
Approximate Unit Weight (kg)	2.7	3.7
Approximate No. per m ²	48.5	48.5
No. Per Pack	264	264
Pack Weight (kg) ¹	734	1006
Characteristic Unconfined Compressive Strength (MPa) <i>f'uc</i>	>10	>10
Cold Water Absorption (%)	<15	<15
Coefficient of Expansion (mm/m)	<0.8	<0.8
Durability Class	General Purpose	General Purpose
Initial Rate of Absorption (kg/m ² /min)	<1.6	<1.6
Potential to Effloresce	Nil-Slight	Nil-Slight
Liability to Lime Pitting	Nil	Nil
Core Percentage	<30	-
Solar Absorption Rating	Low	Low
Fire Resistance – Insulation (minutes)	90	90

This technical information represents average properties obtained from production runs. If specific results are required, samples should be taken from current production runs. AS/NZS 4456 and 4586 are used as applicable. Durability classifications are based on product knowledge under local (Perth) climatic condition. Colours are indicative only. Information subject to change without notice.

¹Includes +3% moisture

Midland Creams – Clay Face Bricks



Cream Mexi



Cream Mexi Coach




Cream Smooth



Desert Oak



Limestone Hue



Milano



Seville



Tuscan

Note: If you require specific or improved product specifications please contact your Sales Representative.

DISCLAIMER. The information presented herein is supplied in good faith and to the best of our knowledge was correct at the time of preparation. No responsibility can be accepted by Midland Brick Company Pty Ltd, its staff or its agents for any errors or omissions. Users are advised to make their own determination as to the suitability of this information in relation to their particular purposes and specific circumstances. Since the information contained in this document may be applied under conditions beyond our control, no responsibility can be accepted by Midland Brick Company Pty Ltd, its staff or its agents for any loss or damage caused by any person acting or refraining from action as a result of this information.


Product Data Sheet

Midland Brick

A BORAL COMPANY

CLAY FACE BRICK

Milano Midland Creams



Product Information	Cored	Solid
Work Size (mm)	230 x 110 x 76	230 x 110 x 76
Dimensional Category	DW1	DW1
Approximate Unit Weight (kg)	2.6	3.7
Approximate No. per m ²	48.5	48.5
No. Per Pack	264	264
Pack Weight (kg) ¹	707	1006
Characteristic Unconfined Compressive Strength (MPa) <i>f'uc</i>	>12	>12
Cold Water Absorption (%)	<15	<15
Coefficient of Expansion (mm/m)	<0.8	<0.8
Durability Class	General Purpose	General Purpose
Initial Rate of Absorption (kg/m ² /min)	<1.6	<1.6
Potential to Effloresce	Nil-Slight	Nil-Slight
Liability to Lime Pitting	Nil	Nil
Core Percentage	<30	-
Solar Absorption Rating	Low	Low
Fire Resistance – Insulation (minutes)	90	90

This technical information represents average properties obtained from production runs. If specific results are required, samples should be taken from current production runs. AS/NZS 4456 and 4586 are used as applicable. Durability classifications are based on product knowledge under local (Perth) climatic condition. Colours are indicative only. Information subject to change without notice.

¹Includes +3% moisture

Midland Creams – Clay Face Bricks



Cream Mexi



Cream Mexi Coach




Cream Smooth



Desert Oak



Limestone Hue



Milano



Seville



Tuscan

Note: If you require specific or improved product specifications please contact your Sales Representative.

DISCLAIMER. The information presented herein is supplied in good faith and to the best of our knowledge was correct at the time of preparation. No responsibility can be accepted by Midland Brick Company Pty Ltd, its staff or its agents for any errors or omissions. Users are advised to make their own determination as to the suitability of this information in relation to their particular purposes and specific circumstances. Since the information contained in this document may be applied under conditions beyond our control, no responsibility can be accepted by Midland Brick Company Pty Ltd, its staff or its agents for any loss or damage caused by any person acting or refraining from action as a result of this information.


Product Data Sheet

Midland Brick

A BORAL COMPANY

CLAY FACE BRICK

Seville Midland Creams



Product Information	Cored	Solid
Work Size (mm)	230 x 110 x 76	230 x 110 x 76
Dimensional Category	DW1	DW1
Approximate Unit Weight (kg)	2.7	3.7
Approximate No. per m ²	48.5	48.5
No. Per Pack	264	264
Pack Weight (kg) ¹	734	1006
Characteristic Unconfined Compressive Strength (MPa) <i>f'</i> _{uc}	>12	>12
Cold Water Absorption (%)	<12	<12
Coefficient of Expansion (mm/m)	<0.8	<0.8
Durability Class	General Purpose	General Purpose
Initial Rate of Absorption (kg/m ² /min)	<1.4	<1.4
Potential to Effloresce	Nil-Slight	Nil-Slight
Liability to Lime Pitting	Nil	Nil
Core Percentage	<30	-
Solar Absorption Rating	Low	Low
Fire Resistance – Insulation (minutes)	90	90

This technical information represents average properties obtained from production runs. If specific results are required, samples should be taken from current production runs. AS/NZS 4456 and 4586 are used as applicable. Durability classifications are based on product knowledge under local (Perth) climatic condition. Colours are indicative only. Information subject to change without notice.

¹Includes +3% moisture

Midland Creams – Clay Face Bricks



Cream Mexi



Cream Mexi Coach




Cream Smooth



Desert Oak



Limestone Hue



Milano



Seville



Tuscan

Note: If you require specific or improved product specifications please contact your Sales Representative.

DISCLAIMER. The information presented herein is supplied in good faith and to the best of our knowledge was correct at the time of preparation. No responsibility can be accepted by Midland Brick Company Pty Ltd, its staff or its agents for any errors or omissions. Users are advised to make their own determination as to the suitability of this information in relation to their particular purposes and specific circumstances. Since the information contained in this document may be applied under conditions beyond our control, no responsibility can be accepted by Midland Brick Company Pty Ltd, its staff or its agents for any loss or damage caused by any person acting or refraining from action as a result of this information.


Product Data Sheet

Midland Brick

A BORAL COMPANY

CLAY FACE BRICK

Tuscan Midland Creams



Product Information	Cored	Solid
Work Size (mm)	230 x 110 x 76	230 x 110 x 76
Dimensional Category	DW1	DW1
Approximate Unit Weight (kg)	2.6	3.6
Approximate No. per m ²	48.5	48.5
No. Per Pack	264	264
Pack Weight (kg) ¹	707	979
Characteristic Unconfined Compressive Strength (MPa) <i>f'</i> _{uc}	>10	>10
Cold Water Absorption (%)	<12	<12
Coefficient of Expansion (mm/m)	<0.8	<0.8
Durability Class	Exposure Grade - Marine	Exposure Grade - Marine
Initial Rate of Absorption (kg/m ² /min)	<1.4	<1.4
Potential to Effloresce	Nil-Slight	Nil-Slight
Liability to Lime Pitting	Nil	Nil
Core Percentage	<30	-
Solar Absorption Rating	Low	Low
Fire Resistance – Insulation (minutes)	90	90

This technical information represents average properties obtained from production runs. If specific results are required, samples should be taken from current production runs. AS/NZS 4456 and 4586 are used as applicable. Durability classifications are based on product knowledge under local (Perth) climatic condition. Colours are indicative only. Information subject to change without notice.

¹Includes +3% moisture

Midland Creams – Clay Face Bricks



Cream Mexi



Cream Mexi Coach




Cream Smooth



Desert Oak



Limestone Hue



Milano



Seville



Tuscan

Note: If you require specific or improved product specifications please contact your Sales Representative.

DISCLAIMER. The information presented herein is supplied in good faith and to the best of our knowledge was correct at the time of preparation. No responsibility can be accepted by Midland Brick Company Pty Ltd, its staff or its agents for any errors or omissions. Users are advised to make their own determination as to the suitability of this information in relation to their particular purposes and specific circumstances. Since the information contained in this document may be applied under conditions beyond our control, no responsibility can be accepted by Midland Brick Company Pty Ltd, its staff or its agents for any loss or damage caused by any person acting or refraining from action as a result of this information.