


MASONRY PAVER

Charcoal Masterpave Classic 60mm






Product Information	
Work Size (mm)	200 x 200 x 60
Dimensional Category	DPA2
CMAA Shape Category	Type C
Approximate Dry Unit Weight (kg)	5.2
Approximate No. per m ²	25
No. Per Pack	230
Nominal Pack Weight (kg) ³	1232
Breaking Load (kN) ¹	>12
Mean Abrasion Index (V _a) ²	<10
Slip Resistance Category	P5
Cold Water Absorption (%)	<5
Coefficient of Contraction (mm/m)	<0.8
Durability Class	General Purpose
Potential to Effloresce	Slight to Moderate
Liability to Lime Pitting	Nil
Solar Absorption Rating	Dark

This technical information represents average properties obtained from productions runs. If specific results are required, samples should be taken from current production runs. AS/NZS 4456 and 4586 are used as applicable. Durability classifications are based on product knowledge under local (Perth) climatic conditions. Colours are indicative only. Information subject to change without notice.

Masterpave Classic 60mm Masonry Paver Range





Other colours available on request

Note: If you require specific or improved product specifications please contact your Sales Representative

¹ At 28 days


² At 90 days

³ Includes +3% for moisture



MASONRY PAVER

Donnybrook Masterpave Classic 60mm






Product Information	
Work Size (mm)	200 x 200 x 60
Dimensional Category	DPA2
CMAA Shape Category	Туре С
Approximate Dry Unit Weight (kg)	5.2
Approximate No. per m²	25
No. Per Pack	230
Nominal Pack Weight (kg) ³	1232
Breaking Load (kN) ¹	>12
Mean Abrasion Index (V _a) ²	<10
Slip Resistance Category	P5
Cold Water Absorption (%)	<5
Coefficient of Contraction (mm/m)	<0.8
Durability Class	General Purpose
Potential to Effloresce	Slight
Liability to Lime Pitting	Nil
Solar Absorption Rating	Medium to Dark

This technical information represents average properties obtained from productions runs. If specific results are required, samples should be taken from current production runs. AS/NZS 4456 and 4586 are used as applicable. Durability classifications are based on product knowledge under local (Perth) climatic conditions. Colours are indicative only. Information subject to change without notice.

Masterpave Classic 60mm Masonry Paver Range











Heritage Red

Morocco

Pewter Steel Grey Other colours available on request Note: If you require specific or improved product specifications please contact your Sales Representative

¹ At 28 days


² At 90 days

³ Includes +3% for moisture



MASONRY PAVER

Golden Sand Masterpave Classic 60mm





Product Information	
Work Size (mm)	200 x 200 x 60
Dimensional Category	DPA2
CMAA Shape Category	Туре С
Approximate Dry Unit Weight (kg)	5.2
Approximate No. per m ²	25
No. Per Pack	230
Nominal Pack Weight (kg) ³	1232
Breaking Load (kN) ¹	>12
Mean Abrasion Index (V _a) ²	<10
Slip Resistance Category	P5
Cold Water Absorption (%)	<5
Coefficient of Contraction (mm/m)	<0.8
Durability Class	General Purpose
Potential to Effloresce	Slight
Liability to Lime Pitting	Nil
Solar Absorption Rating	Light

This technical information represents average properties obtained from productions runs. If specific results are required, samples should be taken from current production runs. AS/NZS 4456 and 4586 are used as applicable. Durability classifications are based on product knowledge under local (Perth) climatic conditions. Colours are indicative only. Information subject to change without notice.

Masterpave Classic 60mm Masonry Paver Range



Charcoal



Donnybrook

Steel Grey



Golden Sand



Heritage Red



Limestone



Morocco



Pewter

Other colours available on request

Note: If you require specific or improved product specifications please contact your Sales Representative

¹ At 28 days


² At 90 days

³ Includes +3% for moisture



MASONRY PAVER

Heritage Red Masterpave Classic 60mm





Product Information	
Work Size (mm)	200 x 200 x 60
Dimensional Category	DPA2
CMAA Shape Category	Туре С
Approximate Dry Unit Weight (kg)	5.2
Approximate No. per m²	25
No. Per Pack	230
Nominal Pack Weight (kg) ³	1232
Breaking Load (kN) ¹	>12
Mean Abrasion Index (V _a) ²	<10
Slip Resistance Category	P5
Cold Water Absorption (%)	<6
Coefficient of Contraction (mm/m)	<0.8
Durability Class	General Purpose
Potential to Effloresce	Slight
Liability to Lime Pitting	Nil
Solar Absorption Rating	Dark

This technical information represents average properties obtained from productions runs. If specific results are required, samples should be taken from current production runs. AS/NZS 4456 and 4586 are used as applicable. Durability classifications are based on product knowledge under local (Perth) climatic conditions. Colours are indicative only. Information subject to change without notice.

Masterpave Classic 60mm Masonry Paver Range



Charcoal



Donnybrook



Golden Sand



Heritage Red



Limestone



Morocco





Other colours available on request

Note: If you require specific or improved product specifications please contact your Sales Representative

¹ At 28 days


² At 90 days

³ Includes +3% for moisture



MASONRY PAVER

Limestone Masterpave Classic 60mm





Product Information	
Work Size (mm)	200 x 200 x 60
Dimensional Category	DPA2
CMAA Shape Category	Type C
Approximate Dry Unit Weight (kg)	5.1
Approximate No. per m ²	25
No. Per Pack	230
Nominal Pack Weight (kg) ³	1208
Breaking Load (kN) ¹	>12
Mean Abrasion Index (V _a) ²	<10
Slip Resistance Category	P5
Cold Water Absorption (%)	<6
Coefficient of Contraction (mm/m)	<0.8
Durability Class	General Purpose
Potential to Effloresce	Nil to Slight
Liability to Lime Pitting	Nil
Solar Absorption Rating	Light

This technical information represents average properties obtained from productions runs. If specific results are required, samples should be taken from current production runs. AS/NZS 4456 and 4586 are used as applicable. Durability classifications are based on product knowledge under local (Perth) climatic conditions. Colours are indicative only. Information subject to change without notice.

Masterpave Classic 60mm Masonry Paver Range







Donnybrook



Golden Sand



Heritage Red



Limestone



Morocco



Pewter



Steel Grey

Other colours available on request

Note: If you require specific or improved product specifications please contact your Sales Representative

¹ At 28 days

² At 90 days


³ Includes +3% for moisture



A BORAL COMPANY

MASONRY PAVER

Morocco Masterpave Classic 60mm





Product Information	
Work Size (mm)	200 x 200 x 60
Dimensional Category	DPA2
CMAA Shape Category	Туре С
Approximate Dry Unit Weight (kg)	5.1
Approximate No. per m ²	25
No. Per Pack	230
Nominal Pack Weight (kg) ³	1208
Breaking Load (kN) ¹	>12
Mean Abrasion Index (V _a) ²	<10
Slip Resistance Category	P5
Cold Water Absorption (%)	<5
Coefficient of Contraction (mm/m)	<0.8
Durability Class	General Purpose
Potential to Effloresce	Slight
Liability to Lime Pitting	Nil
Solar Absorption Rating	Dark

This technical information represents average properties obtained from productions runs. If specific results are required, samples should be taken from current production runs. AS/NZS 4456 and 4586 are used as applicable. Durability classifications are based on product knowledge under local (Perth) climatic conditions. Colours are indicative only. Information subject to change without notice.

Masterpave Classic 60mm Masonry Paver Range







Donnybrook



Golden Sand



Heritage Red



Limestone



Morocco



Pewter Steel Grey

Other colours available on request

Note: If you require specific or improved product specifications please contact your Sales Representative

¹ At 28 days


² At 90 days

³ Includes +3% for moisture



MASONRY PAVER

Pewter Masterpave Classic 60mm






Product Information	
Work Size (mm)	200 x 200 x 60
Dimensional Category	DPA2
CMAA Shape Category	Type C
Approximate Dry Unit Weight (kg)	5.2
Approximate No. per m ²	25
No. Per Pack	230
Nominal Pack Weight (kg) ³	1232
Breaking Load (kN) ¹	>12
Mean Abrasion Index (V _a) ²	<10
Slip Resistance Category	P5
Cold Water Absorption (%)	<6
Coefficient of Contraction (mm/m)	<0.8
Durability Class	General Purpose
Potential to Effloresce	Slight
Liability to Lime Pitting	Nil
Solar Absorption Rating	Medium

This technical information represents average properties obtained from productions runs. If specific results are required, samples should be taken from current production runs. AS/NZS 4456 and 4586 are used as applicable. Durability classifications are based on product knowledge under local (Perth) climatic conditions. Colours are indicative only. Information subject to change without notice.

Masterpave Classic 60mm Masonry Paver Range











ne Morocco

Pewter Steel Grey Other colours available on request Note: If you require specific or improved product specifications please contact your Sales Representative

¹ At 28 days


² At 90 days

³ Includes +3% for moisture



MASONRY PAVER

Steel Grey Masterpave Classic 60mm





Product Information	
Work Size (mm)	200 x 200 x 60
Dimensional Category	DPA2
CMAA Shape Category	Type C
Approximate Dry Unit Weight (kg)	5.2
Approximate No. per m ²	25
No. Per Pack	230
Nominal Pack Weight (kg) ³	1232
Breaking Load (kN) ¹	>12
Mean Abrasion Index (V _a) ²	<10
Slip Resistance Category	P5
Cold Water Absorption (%)	<6
Coefficient of Contraction (mm/m)	<0.8
Durability Class	General Purpose
Potential to Effloresce	Slight
Liability to Lime Pitting	Nil
Solar Absorption Rating	Medium to Dark

This technical information represents average properties obtained from productions runs. If specific results are required, samples should be taken from current production runs. AS/NZS 4456 and 4586 are used as applicable. Durability classifications are based on product knowledge under local (Perth) climatic conditions. Colours are indicative only. Information subject to change without notice.

Masterpave Classic 60mm Masonry Paver Range







Donnybrook



Golden Sand



Heritage Red



Limestone



Morocco





Other colours available on request

Note: If you require specific or improved product specifications please contact your Sales Representative

¹ At 28 days

² At 90 days

³ Includes +3% for moisture